

TOP SELLING 32.768kHz TIMING COMPONENTS

Featuring Tuning Fork Crystals And Oscillators

*** IN STOCK ***

TOP SELLING 32.768kHz TUNING FORK CRYSTALS AND OSCILLATORS



32.768kHz Tuning Fork Crystals

PART NUMBER	PACKAGE SIZE (mm)		CL, PLATING LOAD (pF)	ESR MAX (kΩ)	TOLERANCE (± ppm)	OPERATING TEMPERATURE RANGE
	L	W				
ABS06-32.768KHZ-T	2.0	1.2	12.5	90	20	-40°C to +85°C
ABS07-32.768KHZ-T	3.2	1.5	12.5	70	20	-40°C to +85°C
ABS07-32.768KHZ-4-T	3.2	1.5	4	70	20	-40°C to +85°C
ABS07-32.768KHZ-6-T	3.2	1.5	6	70	20	-40°C to +85°C
ABS07-32.768KHZ-7-T	3.2	1.5	7	70	20	-40°C to +85°C
ABS07-32.768KHZ-9-T	3.2	1.5	9	70	20	-40°C to +85°C
ABS13-32.768KHZ-T	6.9	1.4	12.5	65	20	-40°C to +85°C
ABS25-32.768KHZ-T	8.0	3.8	12.5	50	20	-40°C to +85°C
ABS25-32.768KHZ-6-T	8.0	3.8	6	50	20	-40°C to +85°C
ABS25-32.768KHZ-6-1-T	8.0	3.8	6	50	10	-40°C to +85°C
ABS25-32.768KHZ-1-T	8.0	3.8	12.5	50	10	-40°C to +85°C
AB26TRB-32.768KHZ-T	6.0	Ø1.9	12.5	50	10	-40°C to +85°C
AB26T-32.768KHZ	6.2	Ø2.1	12.5	35	20	-10°C to +60°C

32.768kHz Oscillators

PART NUMBER	PACKAGE SIZE (mm)		VDD (V)	OUTPUT LOGIC TYPE	OPERATING TEMPERATURE RANGE
	L	W			
ASDK2-32.768KHZ-LR-T	2.5	2.0	1.8	CMOS	-40°C to +85°C
ASEK-32.768KHZ-LR-T	3.2	2.5	3.3	CMOS	-40°C to +85°C